



N NETPROO®

BE ALERT, BE SAFE....



PRODUCT CATALOGUE

- IP CAMERAS & NVRs
- AHD CAMERAS & DVRs
- CCTV CABLES & CAT-6
- CCTV POWER SUPPLY
- NETWORK POE SWITCHES



MAKE IN INDIA

www.netproo.com

SILVER 4MP IP COLOR CAMERA

NT-2.0 DOME (4MP)



1/3", 4MP low illumination, CMOS sensor, 2.8MM Lens WDR (Off/Low/Middle/High), Resolution 3MP (2304*1296@20fps), 2MP (1920*1080@25fps, 720P (1920*720)25fps is optional, support NTSC 2MP@30fps, Built-in humanoid detection algorithm; Detection frame 5fps, detect 5 people at the same time; Low consumption, low code stream, low delay; S.265 compression format, save bandwidth and storage space; Support Smart IR to avoid Infrared over-exposure at night; Support ICR auto switch, achieve best result for D&N video; Support PoE Support 3D DNR and digital WDR; Support auto-electronic shuttle to suit different

NT-2.0 BULLET (4MP)



1/3", 4MP low illumination CMOS sensor, 2.8MM Lens WDR (Off/Low/Middle/High), Resolution 3MP (2304*1296@20fps), 2MP (1920*1080@25fps, 720P (1920*720)25fps is optional, support NTSC 2MP@30fps, Built-in humanoid detection algorithm; Detection frame 5fps, detect 5 people at the same time; Low consumption, low code stream, low delay; S.265 compression format, save bandwidth and storage space; Support Smart IR to avoid Infrared over-exposure at night; Support ICR auto switch, achieve best result for D&N video; Support PoE (option) Support 3D DNR and digital WDR; Support auto-electronic shuttle to suit

GOLD 5MP IP COLOR CAMERA

NT-5.5A DOME GOLD



Key Feature:

- 1/2.7", 5MP low illumination
- CMOS sensor
- 2.8MM Lens Human detection
- S.265/H.265/H.264 compression format
- Max 5MP 2592*1944 @25fps
- D-WDR, 3D DNR
- Support 4 kinds of lights mode: dual light, warm Light , Infrared CDS or Sensor Trigger
- Support ONVIF
- Support to draw area to detect alarm

NT-5.5A BULLET GOLD



Key Feature:

- 1/2.7", 5MP low illumination
- CMOS sensor
- 2.8MM Lens Human detection
- S.265/H.265/H.264 compression format
- Max 5MP 2592*1944 @25fps
- D-WDR, 3D DNR
- Support 4 kinds of lights mode: dual light, warm Light , Infrared CDS or Sensor Trigger
- Support ONVIF
- Support to draw area to detect alarm

NT-5.5A DOME GOLD TOWAY



Key Feature:

- 1/2.7", 5MP low illumination
- CMOS sensor
- Human detection
- S.265/H.265/H.264 compression format
- Max 5MP 2592*1944 @25fps
- Built-in amplifier board
- Support Two-way Intercom and human alert
- voice Broadcast, D-WDR & 3D DNR
- Support 4 kinds of lights mode: dual light warm Light , Infrared CDS or Sensor Trigger
- Support ONVIF
- Support to draw area to detect alarm

NT-5.5A BULLET GOLD TOWAY



Key Feature:

- 1/2.7", 5MP low illumination
- CMOS sensor
- Human detection
- S.265/H.265/H.264 compression format
- Max 5MP 2592*1944 @25fps
- Built-in amplifier board
- Support Two-way Intercom and human alert
- voice Broadcast, D-WDR & 3D DNR
- Support 4 kinds of lights mode: dual light warm Light , Infrared CDS or Sensor Trigger
- Support ONVIF
- Support to draw area to detect alarm

PRO 6/8MP IP COLOR CAMERA

NT-6.0 DOME PRO



Key Feature:

- 1/2.8", 6MP low illumination
- CMOS sensor, Support area Intrusion,
- Line-Crossing detection ,loitering,
- Absent alarm, vehicle illegal parking,
- Vehicle retrograde, Built-in human
- Detection algorithm, Detection frame
- 5fps, detect 5-10 people at the same
- Time, Low consumption, low code stream,
- Low delay, Support auto-electronic
- Shuttle to suit different surveillance
- Environment, Support Alarm Recording
- Linkage, Support two-way audio intercom,
- Support Onvif, email, NTP service ,
- Support HTTPS encrypted transmission

NT-6.0 BULLET PRO



Key Feature:

- 1/2.8", 6MP low illumination
- CMOS sensor, Support area Intrusion,
- Line-Crossing detection ,loitering,
- absent alarm, vehicle illegal parking,
- Vehicle retrograde, Built-in human
- detection algorithm, Detection frame
- 5fps, detect 5-10 people at the same
- time, Low consumption, low code stream,
- low delay, Support auto-electronic
- shuttle to suit different surveillance
- environment, Support Alarm Recording
- Linkage, Support two-way audio intercom,
- Support ONVIF, email, NTP service ,
- Support HTTPS encrypted transmission

NT-8.0 DOME PRO



Key Feature:

- 1/2.7", 8MP low illumination
- CMOS sensor, 8MP 3840*2160@25fps,
- Support Area Intrusion,
- Line-Crossing Detection, Loitering,
- Absent Alarm, Vehicle Illegal Parking,
- Vehicle Retrograde, Built-in human
- Detection algorithm, Detection frame
- 5fps, detect 5-10 people at the same
- Time, Low consumption, low code stream,
- Low delay, Support ICR auto switch,
- Achieve best result for D&N video,
- Support two-way audio intercom,
- Support Onvif, email, NTP service ,
- Change the password during initial use to ensure the security of the password

NT-8.0 BULLET PRO



Key Feature:

- 1/2.7", 8MP low illumination
- CMOS sensor, 8MP 3840*2160@25fps,
- Support Area Intrusion,
- Line-Crossing Detection, Loitering,
- Absent Alarm, Vehicle Illegal Parking,
- Vehicle Retrograde, Built-in human
- Detection algorithm, Detection frame
- 5fps, detect 5-10 people at the same
- Time, Low consumption, low code stream,
- Low delay, Support ICR auto switch,
- Achieve best result for D&N video,
- Support two-way audio intercom,
- Support Onvif, email, NTP service ,
- Change the password during initial use to ensure the security of the password

5/8MP IP MOTORIZED CAMERA

NEW

NP-IP-5MP-MVF 50MTR IR



Key Feature:

- 1/2.8", 5 Mega Pixel CMOS Image Sensor
- Lens (MOTERISED 2.8mm TO 12MM.)
- Maximum 25 fps
- Support: POE
- H.265/H.265+ Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-65 Weather-proof
- Support Audio Optional
- Dual Light

NEW

NP-IP-8MP-MVF 50MTR IR



Key Feature:

- 1/2.8", 8 Mega Pixel CMOS Image Sensor
- Lens (MOTERISED 2.8mm TO 12MM.)
- Maximum 25 fps
- Support: POE
- H.265/H.265+ Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-65 Weather-proof
- Support Audio Optional
- Dual Light

4/5MP IP CAMERA (6/8MM) LENS

NP-IP-4MP-6MM / 8MM



Key Feature:

- 1/2.7", 4 Mega Pixel CMOS Image Sensor
- Lens 6mm / 8mm
- Maximum 25 fps
- Support: POE
- H.265/H.265+ Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-66 Weather-proof
- Support Audio Optional

NP-IP-5MP-6MM / 8MM



Key Feature:

- 1/2.7", 5 Mega Pixel CMOS Image Sensor
- Lens 6mm / 8mm
- Maximum 25 fps
- Support: POE
- H.265/H.265+ Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-66 Weather-proof
- Support Audio Optional

4/5MP IP CAMERA (12MM) LENS

NP-IP-4MP-6MM / 8MM



Key Feature:

- 1/2.7", 4 Mega Pixel CMOS Image Sensor
- Lens 12mm
- Maximum 25 fps
- Support: POE
- H.265/H.265+ Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-66 Weather-proof
- Support Audio Optional

NP-IP-5MP-6MM / 8MM



Key Feature:

- 1/2.7", 5 Mega Pixel CMOS Image Sensor
- Lens 12mm
- Maximum 25 fps
- Support: POE
- H.265/H.265+ Dual Stream.
- Color Night Vision
- 3DDNR, AGC, AWB, BLC Supported
- IP-66 Weather-proof
- Support Audio Optional

VARIFOCAL 5MP IP COLOR CAMERA

VERIFOCAL NT 5.5VF



1/2.7", 5MP low illumination CMOS sensor, Support motorized lens, auto focus, Resolution 5MP(2592*1904@20fps), 2.8MM TO 13.5MM ZOOM Built-in humanoid detection algorithm; Detection frame 5fps, detect 5 people at the same time; Low consumption, low code stream, low delay; S.265 compression format, save bandwidth and storage space; Support Smart IR to avoid Infrared over-exposure at night;

DARKFIGHTER NT 5.0 AI



Resolution 5MP 2592*1904 Built-in amplifier board; Support area Intrusion, Line-Crossing detection, loitering, absent alarm, vehicle illegal parking, Vehicle retrograde Built-in humanoid detection algorithm; Detection frame 5fps, detect 5-10 people at the same time; Low consumption, low code stream, low delay; S.265 compression format, save bandwidth and storage space; Support Smart IR to avoid Infrared over-exposure at night; Support ICR auto switch, achieve best result for D&N video; Support PoE

PTZ 4/6 MP CAMERA

NT-PTZ-4036X-M



4 MP 1/2.8" CMOS; Color 0.01Lux@F1.2, Black and White 0.001Lux@F1.2, 36X optical zoom, IR distance up to 150 meters Auto white balance; Auto exposure; Backlight compensation; Support D-WDR; Electronic defogging; Daylight anti-flash, Wide: Diagonal 62.0° Horizontal: 54.8° Vertical: 31.5° Tele: Diagonal 4.1° Horizontal: 3.59° Vertical: 2.03°, F1.8~F3.9, Support H.265+/H.265/H.264; Support dual stream and AVI format; Code stream 0.1M~8Mbps adjustable; Frame rate 1~30 fps adjustable, Support RTSP/ FTP/ DHCP/ NTP/ UPNP/ Onvif/ HIKVISION private protocol, 1 RJ45 10 M / 100 M Ethernet interface, TF card support upto 512gb, preset support 220, DC : 12V±25 also support POE

NT-PTZ-6036X-M



6MP 1/2.8" IMX335 SONY ; Color 0.0001Lux@F1.2, Black and White ,36X optical zoom, IR distance up to 150 meters Auto white balance; Auto exposure; Backlight compensation; Support D-WDR; Electronic defogging; Daylight anti-flash, Wide: Diagonal 62.0° Horizontal: 54.8° Vertical: 31.5° Tele: Diagonal 4.1° Horizontal: 3.59° Vertical: 2.03°, F1.8~F3.9, Support H.265+/H.265/H.264; Support dual stream and AVI format; Code stream 0.1M~8Mbps adjustable; Frame rate 1~30 fps adjustable, Support

IP LONG DISTANCE PTZ CAMERA

HDC-IP-4MP-PTZ



Key Feature:

- 4MP, 36X Zoom
- Zoom Display 36X, Neutral Package
- 6 inch, Half Metal Body Construction, IP66
- IP-PTZ AI Medium speed dome
- IR Sidtance Up to 150 meters
- Wall Mount Bracket, DC12V Power Supply

HDC-IP-5MP-PTZ



Key Feature:

- 5MP, 36X Zoom
- Zoom Display 36X, Neutral Package
- 7 inch, Half Metal Body Construction, IP66
- IP-PTZ AI Medium speed dome
- IR Sidtance Up to 200 meters
- Wall Mount Bracket, DC12V Power Supply

HDC-IP-6MP-PTZ



Key Feature:

- 6MP, 36X Zoom
- Zoom Display 36X, Neutral Package
- 10 inch, Half Metal Body Construction, IP66
- IP-PTZ AI Medium speed dome
- IR Sidtance Up to 150 meters
- Wall Mount Bracket, DC12V Power Supply

10/16 CHANNEL NVR

NP-NVR-10CH-H265-4K

Support access of multiple NetProo smart IP Cameras with human detection and face detection function.



10CH IPC input (8MP/D1+10CH Preview+4CH Playback, Smart265, H265, H264 decoding format, synchronized recording, remote view, backup recording in MP4 format, mobile view,VGA/HDMI output, preview image and playback image electronic amplification, Line-crossing detection, Vehicle retrograde, Staff absence, Loitering, Area intrusion, Vehicle illegal parking, 10CH 4K decoding and 4K display output, incoming bandwidth up to 80M

NP-NVR-16CH-H265-4K

Support access of multiple NetProo smart IP Cameras with human detection and face detection function.



16 CH IPC input,Smart265, H265, H264 decoding format, synchronized recording, remote view, backup recording in Mp4 format, mobile view,VGA/HDMI output, preview image and playback image electronic amplification, Line-crossing detection, Vehicle retrograde, Staff absence, Loitering, Area intrusion, Vehicle illegal parking, 16 CH 4K decoding and 4K display output, incoming bandwidth up to 150M

36/64 CHANNEL NVR

NP-NVR-36CH-H265-4K

Support access of multiple NetProo smart IP Cameras with human detection and face detection function.



36CH IPC input Smart265, H265, H264 decoding format, synchronized recording, remote view, backup recording in Mp4 format, mobile view, VGA/HDMI output, preview image and playback image electronic amplification, standard ONVIF, RTSP, GB28181 protocol, RTMP, alarm capture, alarm email sending function, DDNS, UPNP, NTP, P2P, WEB, mobile view, IMS surveillance, IPC smart analysis including line-crossing detection, vehicle retrograde, staff absence, loitering, area intrusion, vehicle illegal parking, channel cruise grouping, network inspection including network traffic monitoring and network diagnosis, maximum 9CH synchronous playback, fast booting, new UI interface with smooth operation, 36CH 4K decoding and 4K display output, add IPC manually or automatically in LAN, upgrade IPC online or via U disk, maintain IPC under private protocol including restore, restart, enable or disable all netcom functions, new optimization for high quality compatibility with hard disks on the market, ANR (Automatic Network Replenishment) function, select the video stream mode, optimized incoming bandwidth up to 220M.

NP-NVR-64CH-H265-4K

Support access of multiple NetProo smart IP Cameras with human detection and face detection function.



H.265+ 64CH IVR system with 64CH 4K IP camera input/output, smart IPC analysis, 9 HDDs (max 16TB), VGA/HDMI, USB, mobile view, alarm/audio, and 4CH IO alarms. Features include 36CH/64CH IPC input with preview/playback, H265/H264/H265+ compression, synchronized recording, RTSP, ONVIF, HTTP, RTMP, electronic zoom, email alerts, DDNS, P2P, IMS, and HTML5 access. Advanced analytics cover intrusion, loitering, line-crossing, and more. Includes network inspection, 4CH 1080P playback, IPC upgrades, restore/restart functions, 512M optimized bandwidth, and 64 split screens for comprehensive surveillance control.

4/8 CHANNEL DVR

NP-4CH-5MPDVR-H265

Digital Video Recorder (DVR)
with Smart Analytics Function



Key Feature:

- Operation: Embedded Linux
- Operation System
- Resolution: 4 Ch(5mp)
- Video Compression: H.265
- Video Output: 1-VGA, 1-HDMI
- Coaxial audio : support
- Image Display: 1/4
- Video Speed: 5mp, 22fps
- Supports: CVBS, AHD, IP, CVI, TVI
- Hard Disk Interface: 1 SATA Up to 6TB
- Recording: Manual, Timing, Alarm, Motion Detection
- USB Interface: 2 USB 2.0
- Power: D.C. 12V
- Wi-Fi Support: Yes

NP-8CH-5MPDVR-H265

Digital Video Recorder (DVR)
with Smart Analytics Function



Key Feature:

- Operation: Embedded Linux
- Operation System
- Resolution: 8Ch(5mp)
- Video Compression: H.265
- Video Output: 1-VGA, 1-HDMI
- Coaxial audio : support
- Image Display: 1/4
- Video Speed: 5mp, 22fps
- Supports: CVBS, AHD, IP, CVI, TVI
- Hard Disk Interface: 1 SATA Up to 6TB
- Recording: Manual, Timing, Alarm, Motion Detection
- USB Interface: 2 USB 2.0
- Power: D.C. 12V
- Wi-Fi Support: Yes

16/32 CHANNEL DVR

NP-16CH-5MPDVR-H265

Digital Video Recorder (DVR)
with Smart Analytics Function



Key Feature:

- Operation: Embedded Linux
- Operation System
- Resolution: 16Ch (5mp)
- Video Compression: H.264
- Video Output: 1-VGA, 1-HDMI
- Coaxial audio : support
- Image Display: 1/4
- Video Speed: 5mp, 22fps
- Supports: CVBS, AHD, IP, CVI, TVI
- Hard Disk Interface: 2 SATA Up to 6TB
- Recording: Manual, Timing, Alarm, Motion Detection
- USB Interface: 2 USB 2.0
- Power: D.C. 12V
- Wi-Fi Support: Yes

NP-32CH-5MPDVR-H265

Digital Video Recorder (DVR)
with Smart Analytics Function



Key Feature:

- Operation: Embedded Linux
- Operation System
- Resolution: 32Ch (5mp)
- Video Compression: H.264
- Video Output: 1-VGA, 1-HDMI
- Coaxial audio : support
- Image Display: 1/4
- Video Speed: 5mp, 22fps
- Supports: CVBS, AHD, IP, CVI, TVI
- Hard Disk Interface: 4 SATA Up to 6TB
- Recording: Manual, Timing, Alarm, Motion Detection
- USB Interface: 2 USB 2.0
- Power: D.C. 12V
- Wi-Fi Support: Yes

HD 2.4 IR DOME & BULLET CAMERA

NP-IR-2.4-D



2.4MP DOME

- 1/2.9", 2.4 Mega Pixel CMOS Sensor
- Resolution: 1920(H) x 1080(V)
- Lens: 3.6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Up to 20m IR Distance
- Multiple Angle Adjustable

NP-IR-2.4-T



2.4MP BULLET

- 1/2.9", 2.4 Mega Pixel CMOS Sensor
- Resolution: 1920(H) x 1080(V)
- Lens: 3.6/6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Up to 20m IR Distance
- Multiple Angle Adjustable

NP-IR-5MP-D



5MP DOME

- 1/3", 5.0 Mega Pixel CMOS Sensor
- Lens: 3.6mm (Fixed)
- Resolution: 2592(H) x 1920(V)
- Up to 20m IR Distance
- Multiple Angle Adjustable
- UTC 4-in-1 - AHD/TVI/CVI/CVBS

NP-IR-5MP-T



5MP BULLET

- 1/3", 5.0 Mega Pixel CMOS Sensor
- Lens: 3.6mm/6mm (Fixed)
- Resolution: 2592(H) x 1920(V)
- Up to 20m IR Distance
- Multiple Angle Adjustable
- UTC 4-in-1 - AHD/TVI/CVI/CVBS

2.4MP HD COLOR CAMERA

2.4MP NP-AHD-CV-2.4-D



Key Feature:

- 1/2.9", 2.4 Mega Pixel CMOS Sensor
- Resolution: 1920(H) x 1080(V)
- Lens: 3.6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Up to 20m IR Distance
- Multiple Angle Adjustable

2.4MP NP-AHD-CV-2.4-T



Key Feature:

- 1/2.9", 2.4 Mega Pixel CMOS Sensor
- Resolution: 1920(H) x 1080(V)
- Lens: 3.6/6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Up to 20m IR Distance
- Multiple Angle Adjustable

2.4MP NP-AHD-CV-2.4-DA



Key Feature:

- 1/2.9", 5.0 Mega Pixel CMOS Sensor
- Lens: 3.6mm (Fixed)
- Resolution: 2592(H) x 1920(V)
- Up to 20m IR Distance
- Multiple Angle Adjustable
- UTC 4-in-1 - AHD/TVI/CVI/CVBS

2.4MP NP-AHD-CV-2.4-TA



Key Feature:

- 1/3", 5.0 Mega Pixel CMOS Sensor
- Lens: 3.6mm/6mm (Fixed)
- Resolution: 2592(H) x 1920(V)
- Up to 20m IR Distance
- Multiple Angle Adjustable
- UTC 4-in-1 - AHD/TVI/CVI/CVBS

5MP HD COLOR CAMERA

5 MP NP-AHD-CV-05-D



Key Feature:

- STARLIGHT 1/2.9", 5 Mega Pixel CMOS Sensor
- Resolution: 2560(H) x 1920(V)
- Lens: 3.6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Min. Illumination: 0.01 Lux/F1.2
- Multiple Angle Adjustable

5 MP NP-AHD-CV-05-T



Key Feature:

- STARLIGHT 1/2.9", 5 Mega Pixel CMOS Sensor
- Resolution: 2560(H) x 1920(V)
- Lens: 3.6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Min. Illumination: 0.01 Lux/F1.2
- Multiple Angle Adjustable

5 MP NP-AHD-CV-05-DA



Key Feature:

- STARLIGHT 1/2.9", 5 Mega Pixel CMOS Sensor
- Resolution: 2560(H) x 1920(V)
- Lens: 3.6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Min. Illumination: 0.01 Lux/F1.2
- Multiple Angle Adjustable
- With Inbuilt Audio Mic

5 MP NP-AHD-CV-05-TA



Key Feature:

- STARLIGHT 1/2.9", 5 Mega Pixel CMOS Sensor
- Resolution: 2560(H) x 1920(V)
- Lens: 3.6mm (Fixed)
- UTC 4-in-1 - AHD/TVI/CVI/CVBS
- Min. Illumination: 0.01 Lux/F1.2
- Multiple Angle Adjustable
- With Inbuilt Audio Mic

CABLES

INDOOR CAT6 CABLE



Key Feature:

- 4 Pair
- 24 AWG
- Weather Proof Single Jacket
- Solid 100% Copper
- Colors: Green , Red, Grey, Yellow

OUTDOOR CAT CABLE



Key Feature:

- 4 Pair
- 24 AWG
- Weather Proof Double Coated
- Solid 100% Copper
- Colors: Green , Red, Grey, Yellow

3+1 CABLE



Key Feature:

- No of Core: Three, Insulation: PVC
- Length: 22 Gauge
- Video Core insulation: HDPE
- Color Video Code: Natural
- Color of Jacket: Black
- Color Jacketing : White
- Shielded: AL-Mylar
- Sequential marking: Every Meter

4+1 CABLE



Key Feature:

- No of Core: Four, Insulation: PVC
- Length: 22 Gauge
- Video Core insulation: HDPE
- Color Video Code: Natural
- Color of Jacket: Black
- Color Jacketing : White
- Shielded: AL-Mylar
- Sequential marking: Every Meter

SMPS POWER SUPPLY

NP-PS04-SINGLE



NP-PS04-SINGLE



NP-PS04-SINGLE



NP-PS04-MULTI



NP-PS08-MULTI



NP-PS16-MULTI



Key Feature:

- Input Voltage : AC 110-285V
- Input Frequency : 50Hz
- Output Voltage : DC 12V- DC 15V
- Output power On : >85%
- Line Regulation : <1%
- Input Cord : 2 Pin
- Input Current : 200 mA @230V
- Output current : 4800 mA Max.

Key Feature:

- Input Voltage : AC 110-285V
- Input Frequency : 50Hz
- Output Voltage : DC 12V- DC 15V
- Output power On : >85%
- Line Regulation : <1%
- Input Cord : 2 Pin
- Input Current : 290 mA @230V
- Output current : 7200 mA Max

Key Feature:

- Input Voltage : AC 110-285V
- Input Frequency : 50Hz
- Output Voltage : DC 12V- DC 15V
- Output power On : >85%
- Line Regulation : <1%
- Input Cord : 2 Pin
- Input Current : 590 mA @230V
- Output current : 9600 mA Max.

Key Feature:

- Input Voltage : AC 110-285V
- Input Frequency : 50Hz
- Output Voltage : DC 12V- DC 15V
- Output power On : >85%
- Line Regulation : <1%
- Input Cord : 2 Pin
- Input Current : 200 mA @230V
- Output current : 4800 mA Max.

Key Feature:

- Input Voltage : AC 110-285V
- Input Frequency : 50Hz
- Output Voltage : DC 12V- DC 15V
- Output power On : >85%
- Line Regulation : <1%
- Input Cord : 2 Pin
- Input Current : 290 mA @230V
- Output current : 7200 mA Max

Key Feature:

- Input Voltage : AC 110-285V
- Input Frequency : 50Hz
- Output Voltage : DC 12V- DC 15V
- Output power On : >85%
- Line Regulation : <1%
- Input Cord : 2 Pin
- Input Current : 590 mA @230V
- Output current : 9600 mA Max.

NETWORK POE SWITCH

UPLINK POE SWITCH (10/100/1000)MBPS

4-PORT

NP-POE-42N



- PoE Ethernet 4*Port: 10/100Mbps
- Ethernet Uplink 2*Port: 100Mbps
- Consumption: 75W(52V 1.44A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 250Mtr.
- Switching Capacity: 1.2Gbps
- Throughput: 0.9Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 0.95Kg

SPEED
10/100MBPS

8-PORT

NP-POE-82N



- PoE Ethernet 8*Port: 10/100Mbps
- Ethernet Uplink 2*Port: 100Mbps
- Consumption: 120W(52V 2.3A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 250Mtr.
- Switching Capacity: 2Gbps
- Throughput: 1.488Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 0.95Kg

SPEED
10/100MBPS

8-PORT

NP-POE-82NGS



- PoE Ethernet 8*Port: 10/100Mbps
- Ethernet Uplink 2*Port: 1000Mbps
- Consumption: 120W(52V 2.3A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 250Mtr.
- Switching Capacity: 5.6Gbps
- Throughput: 4.1664Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 1.05Kg

SPEED
10/100/1000MBPS

16-PORT

NP-POE-1621GS



- PoE Ethernet 16*Port: 10/100Mbps
- Uplink + SFP 2+1*Port: 1000Mbps
- Consumption: 250W(52V 4.8A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 250Mtr.
- Switching Capacity: 7.6Gbps
- Throughput: 5.6544Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 4.2Kg

SPEED
10/100/1000MBPS

24-PORT

NP-POE-24N2G2S



- PoE Ethernet 24*Port: 10/100Mbps
- Uplink + SFP 2+2*Port: 1000Mbps
- Consumption: 300W(52V, 5.76A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 100Mtr.
- Switching Capacity: 12.8Gbps
- Throughput: 9.5232Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 5.2Kg

SPEED
10/100/1000MBPS

FULL GIGA POE SWITCH (1000)MBPS

4-PORT

NP-POE-41FGS



- PoE Ethernet 4*Port: 1000Mbps
- Uplink & SFP Port 1+1: 1000Mbps
- Consumption: 120W(52V 2.3A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 100Mtr.
- Switching Capacity: 12Gbps
- Throughput: 8.928Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 1.05Kg

SPEED
1000MBPS

8-PORT

NP-POE-82FGS



- PoE Ethernet 8*Port: 1000Mbps
- Uplink & SFP 2+2*Port: 1000Mbps
- Consumption: 150W(52V 2.88A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 100Mtr.
- Switching Capacity: 20Gbps
- Throughput: 14.88Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 2.5Kg

SPEED
1000MBPS

FULL GIGA POE SWITCH (1000)MBPS

16-PORT

NP-POE-162G1SF



- PoE Ethernet 16*Port: 1000Mbps
- Uplink + SFP 2+1*Port: 1000Mbps
- Consumption: 300W(52V 5.76A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 250Mtr.
- Switching Capacity: 38Gbps
- Throughput: 29.41Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 4.2Kg

SPEED
1000MBPS

24-PORT

NP-POE-24G1G2GSF




- PoE Ethernet 24*Port: 1000Mbps
- Uplink & SFP 2+2*Port: 1000Mbps
- Consumption: 300W(52V, 5.76A)
- Power Adapter Voltage: AC 110V-240V
- Transmission Distance: 100Mtr.
- Switching Capacity: 56Gbps
- Throughput: 43.34Mbps
- PoE Standard: IEEE802.3af/at
- Color & Weight: Black & 5.68Kg

SPEED
1000MBPS

NNETPROO®

BE ALERT, BE SAFE...



MAKE IN INDIA



www.netproo.com



CE FC RoHS COMPLIANT ISO